

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 July 2005 (21.07.2005)

PCT

(10) International Publication Number  
**WO 2005/067164 A1**

(51) International Patent Classification<sup>7</sup>: **H04B 3/36**,  
3/20, 3/56, 7/015, H03F 3/181, 3/189

(21) International Application Number:  
PCT/NO2005/000013

(22) International Filing Date: 10 January 2005 (10.01.2005)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:  
20040110 9 January 2004 (09.01.2004) NO

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**


- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(71) Applicant and  
(72) Inventor: VAVIK, Geir, Monsen [NO/NO]; Oevre Vikeraunet, N-7057 Jonsvatnet (NO).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

(54) Title: SIGNAL REPEATER SYSTEM



(57) Abstract: Analogue signal repeater system, (1) where frequency converting repeaters (6-9, 10-13) of super-heterodyne or superregenerative type realised with any of discrete semiconductors, MMIC semiconductors, ASIC semiconductors are applied to optimize signal dynamics by avoiding echo between repeaters (6-9, 10-13) and where each information channel (15, 16) in the system only needs two frequency bands, where each second repeater (7, 9, 12, 10) of the signal cascade (2, 14) repeating the signals within the same frequency band to increase isolation against interference between repeaters and against reflections and signal echo.